SPECIFIERS FACT SHEET



Aloha Swim Center Walks & Parking Lot Aloha, Oregon



Distinctively Different

Fine-Grain compared to standard. People friendly appearance, designer friendly too. Use with colors and textures for a dramatic effect as seen below.











Evolution WalkWay™ Fine-Grain Pervious

Performance Data

- Expanded curing options
- Strength: 1800-2200 PSI (ASTM Beta Testing Method)
- Percent voids: Approximately 20% +/- 3% ASTM C 1688
- Permeability: Up to 500 Inches per hour ASTM C1701

General Information

- Listed 2010 Top Ten Most Stainable Products By Sustainable Industries magazine
- Installer Training/Supervision/Certification Required
- Integral color tints available at competitive prices
- Competitive with unit pavers
- Easier to maintain than unit pavers
- Clean with leaf blowers, hoses or pressure washer
- Available as a composite two lift system
- Uses HydroMax® Internal Curing

PO BOX 20610

T:503-393-5050 Toll Free 1-800-357-8217

F: 503-393-0634

Salem, OR 97307

www.evolutionpaving.com

WalkWay™ Customers

- City of Beaverton, Oregon
- City of Eugene, & Eugene School District, Oregon
- City of Olympia, Washington
- City of Longview, Washington
- City of Portland, Oregon
- City of Salem, Oregon
- City of Gresham, Oregon
- Metro, Portland, Oregon
- Portland Water Bureau, & Parks Department
- Tualatin Hills Parks & Recreation District
- Portland Community College
- Willamette Ear Nose & Throat Salem, OR
- Pringle Creek Community Salem, OR
- 2010 Portland Street of Dreams
- City of Hillsboro, Oregon
- City of San Francisco
- City of Tualatin, Oregon
- Milwaukie School District (Oregon)
- Housing Authority Sonoma, California
- And many more

